



Motion C&G P X

Technical Data

Made for

iPhone | iPad | iPod

7X

5X

3X

2X

1X

DX



Earhook

- 77 dB / 135 dB SPL (2 ccm coupler)
- 82 dB / 140 dB SPL (ear simulator)

ThinTube 3.0

- 66 dB / 130 dB SPL (2 ccm coupler)
- 69 dB / 133 dB SPL (ear simulator)

ThinTube 3.0 P

- 70 dB / 131 dB SPL (2 ccm coupler)
- 74 dB / 135 dB SPL (ear simulator)

Data sheet also applicable for Motion C&G P sDemo DX

Motion C&G P X | Technical Data

Type	Earhook	
	2 ccm coupler	Ear simulator
Output sound pressure level		
OSPL 90 at 1.6 kHz	–	136 dB SPL
OSPL 90 (Peak)	135 dB SPL	140 dB SPL
HFA-OSPL 90	130 dB SPL	–
Gain		
FOG at 1.6 kHz	–	77 dB
FOG (peak)	77 dB	82 dB
HFA-FOG	71 dB	–
Reference test gain	53 dB	61 dB
Frequency, noise and directivity		
Frequency range 7X	100 - 6200 Hz	130 - 6300 Hz
5X / 3X / 2X / 1X	100 - 6200 Hz	130 - 6300 Hz
Equivalent input noise	15 dB SPL	15 dB SPL
Total harmonic distortion at 500 / 800 / 1600 / 3200 Hz	4 / 3 / 1 / 1 %	5 / 4 / 1 / – %
Tinnitus Function broadband	80 dB SPL	–
AI-DI	4.0 dB	
Inductive coil sensitivity		
MASL (1 mA/m) at 1.6 kHz	–	106 dB SPL
HFA MASL (1 mA/m)	100 dB SPL	–
HFA SPLITS (left/right)	114 / 114 dB SPL	–
RSETS (left/right)	1 / 1 dB	–
HFA SPLIV	113 dB SPL	–
Battery		
Battery runtime (without streaming)	up to 30 h	
Battery runtime (incl. 5 h streaming)	up to 27 h	
IRIL IEC 60118-13:2016 Ed. 4.0		
700-960 MHz (rating)	user	
1400-2000 MHz (rating)	user	
2000-2700 MHz (rating)	user	
ANSI C63.19-2011		
800-950 MHz (rating)	M4/T4	
1600-2500 MHz (rating)	M4/T4	


Please find additional information to the values on page "Further Information".

Motion C&G P X | Technical Data

Type	ThinTube 3.0		ThinTube 3.0 P	
	2 ccm coupler	Ear simulator	2 ccm coupler	Ear simulator
Output sound pressure level				
OSPL 90 at 1.6 kHz	–	122 dB SPL	–	129 dB SPL
OSPL 90 (Peak)	130 dB SPL	133 dB SPL	131 dB SPL	135 dB SPL
HFA-OSPL 90	117 dB SPL	–	123 dB SPL	–
Gain				
FOG at 1.6 kHz	–	61 dB	–	71 dB
FOG (peak)	66 dB	69 dB	70 dB	74 dB
HFA-FOG	56 dB	–	63 dB	–
Reference test gain	40 dB	47 dB	46 dB	54 dB
Frequency, noise and directivity				
Frequency range 7X 5X / 3X / 2X / 1X	100 - 6200 Hz 100 - 6200 Hz	100 - 6500 Hz 100 - 6500 Hz	100 - 5300 Hz 100 - 5300 Hz	130 - 5200 Hz 130 - 5200 Hz
Equivalent input noise	17 dB SPL	17 dB SPL	17 dB SPL	17 dB SPL
Total harmonic distortion at 500 / 800 / 1600 / 3200 Hz	1 / 1 / 1 / 1 %	1 / 1 / 2 / – %	2 / 1 / 1 / 1 %	3 / 1 / 2 / – %
Tinnitus Function broadband	80 dB SPL	–	80 dB SPL	–
AI-DI	4.0 dB		4.0 dB	
Inductive coil sensitivity				
MASL (1 mA/m) at 1.6 kHz	–	91 dB SPL	–	102 dB SPL
HFA MASL (1 mA/m)	85 dB SPL	–	93 dB SPL	–
HFA SPLITS (left/right)	99 / 99 dB SPL	–	106 / 106 dB SPL	–
RSETS (left/right)	-1 / -1 dB	–	0 / 0 dB	–
HFA SPLIV	99 dB SPL	–	106 dB SPL	–
Battery				
Battery runtime (without streaming)	up to 30 h		up to 30 h	
Battery runtime (incl. 5 h streaming)	up to 27 h		up to 27 h	
IRIL IEC 60118-13:2016 Ed. 4.0				
700-960 MHz (rating)	user		user	
1400-2000 MHz (rating)	user		user	
2000-2700 MHz (rating)	user		user	
ANSI C63.19-2011				
800-950 MHz (rating)	M4/T4		M4/T4	
1600-2500 MHz (rating)	M4/T4		M4/T4	


Please find additional information to the values on page "Further Information".

Motion C&G P X | Fitting Range



Earhook | Basic Data


2 ccm coupler



Max. Output sound pressure level
($L_1 = 90$ dB)


Full on gain
($L_1 = 50$ dB)

Ear simulator




Max. Output sound pressure level
($L_1 = 90$ dB)

Full on gain
($L_1 = 50$ dB)




Frequency response
($L_1 = 60$ dB)




Basic acoustic response
($L_1 = 60$ dB)

Inductive response




Inductive response
($H = 10$ mA/m)



SPLITS curve left ($H = 31.6$ mA/m)


SPLITS curve right
($H = 31.6$ mA/m)






SPLIV curve
($H = 31.6$ mA/m)

ThinTube 3.0 | Basic Data




2 ccm coupler



Ear simulator




Inductive response






ThinTube 3.0 P | Basic Data




2 ccm coupler



Ear simulator



Inductive response



Motion C&G P X | Features and Accessories

	7X	5X	3X	2X	1X
Dynamic Soundscape Processing	■■■■■	■■■■■	■■■■■	■■■■■	■■■■■
OVP (Own Voice Processing) ¹⁾	■■■■■	■■■■■	■■■■■	—	—
Sound Clarity	■■■■■	■■■■■	■■■	■■■	■■
Signal processing (channels) / Gain&MPO (handles)	48 / 20	32 / 16	24 / 12	16 / 8	16 / 8
Hearing programs	6	6	6	4	4
Extended dynamic range	✓	✓	✓	✓	✓
Extended bandwidth	✓	—	—	—	—
EchoShield	✓	—	—	—	—
HD Music (presets)	3	3	1	1	—
eWindScreen ²⁾	Binaural	Binaural	Monaural	Monaural	—
Speech and noise management	✓	✓	✓	✓	✓
SoundSmoothing	✓	✓	✓	✓	—
Feedback cancellation	✓	✓	✓	✓	✓
Speech Quality	■■■■■	■■■■■	■■■	■■	■■
Directionality (Automatic / Adaptive)	Binaural	Binaural	Binaural	✓	✓
Spatial SpeechFocus ^{1) 3)}	✓	✓	—	—	—
TwinPhone ¹⁾	✓	✓	✓	—	—
Frequency compression	✓	✓	✓	✓	✓
Wearer Interaction	■■■■■	■■■■■	■■■■■	■■■■■	■■■■■
Signia App (iOS and Android)	✓	✓	✓	✓	✓
Spatial Configurator	✓	✓	—	—	—
Adaptive Streaming Volume ⁴⁾	✓	✓	✓	✓	✓
Direct Streaming	✓	✓	✓	✓	✓
Made for iPhone	✓	✓	✓	✓	✓
Tinnitus	✓	✓	✓	✓	—
Notched Amplification Therapy	✓	✓	✓	✓	—
Tinnitus noise therapy signal	✓	✓	✓	✓	—
Fitting	✓	✓	✓	✓	✓
Smart Optimizer and Data Logging	✓	✓	✓	✓	✓
Acclimatization manager	✓	✓	✓	✓	✓
InSituGram	✓	✓	✓	✓	✓
AutoFit	✓	✓	✓	✓	✓
TeleCare	✓	✓	✓	✓	✓
Remote Services	✓	✓	✓	✓	✓
Signia App	✓	✓	✓	✓	✓

¹⁾ req. bilateral fitting

²⁾ Binaural used in dedicated programs for 5X

³⁾ for 5X, right / left directionality available only in Stroll Program and via the Spatial Configurator

⁴⁾ streaming only

■■■■■ highest feature performance
 ✓ available — not available ○ optional

Motion C&G P X | Features and Accessories

	7X / 5X / 3X	2X / 1X
Style specific features		
Ingress Protection Rating	IP68	IP68
Charging contacts	✓	✓
Battery Size	—	—
Battery door on/off function	—	—
Nanocoated housing	✓	✓
e2e wireless 3.0	✓	✓
User controls coupling via e2e	✓	✓
Wireless programming	✓	✓
Instrument configurations		
Flat cover	—	—
Rotary volume control	—	—
Push button	—	—
Rocker switch	✓	✓
Color conversion kit	○	○
Color conversion kit with T-Coil	—	—
T-Coil	✓	✓
Battery door – child lock	—	—
Small earhook	○	○
Programming accessories		
ConnexxAir / ConnexxLink	— / —	— / —
Noahlink Wireless	○	○
Programming adapter / cable	—	—
Accessories		
D&C Charger BTE P / Charger BTE P	Mandatory	Mandatory
miniPocket	○	○
StreamLine TV	○	○
StreamLine Mic	○	○
CROS Pure 312 X	○	—
CROS Pure Charge&Go X	○	—
CROS Silk X	—	—

✓ available — not available ○ optional

Motion C&G P X | Further information

Abbreviations

The following abbreviations are used in this datasheet:

SPL	Sound Pressure Level
OSPL	Output Sound Pressure Level
HFA	High Frequency Average
FOG	Full-On Gain
MASL	Magneto Acoustical Sensitivity Level
SPLITS	Coupler SPL for an Inductive Telephone Simulator
RSETS	Relative Equivalent Telephone Sensitivity
SPLIV	SPL In a Vertical magnetic field
AI-DI	Articulation Index - Directivity Index
IRIL	Input Related Interference Level
RTF	Reference Test Frequency

Standards and additional information

- ▶ All measurements with the 2 ccm coupler were performed according to ANSI S3.22-2014 and IEC 60118-0:2015 if applicable.
- ▶ All measurements with an ear simulator were performed according to IEC 118-0/A1:1994 and to DIN 45605 (frequency range) if applicable.
- ▶ Curves and figures representing FOG are measured with 20 dB reduction and 70 dB SPL input level.
- ▶ Figures representing Equivalent Input Noise incorporate a moderate expansion.
- ▶ Tinnitus noiser measurement conditions: all tinnitus single frequency sliders in max position, master volume slider in default position (0 dB) and local volume control in default position.
- ▶ Inductive coil sensitivity values, inductive response curves and T ratings apply for instruments with telecoil only.
- ▶ The current consumption is measured in reference test setting (RTS) according to the applicable standards. Due to the settling behaviour of hearing instruments supporting RF (radio frequency), the battery current is measured 3 minutes after turning on (note: no pairing).
- ▶ The battery runtime is based on first fit settings using 60 % of the fitting range and an ISTS (International Speech Test Signal) input signal at 65 dB SPL (note: pairing established). The actual battery runtime is determined by battery quality, hearing loss, sound environment, usage and activated feature set. Regarding RF usage (Bluetooth streaming) two different conditions are considered.
- ▶ Extended bandwidth up to 12 kHz for 7X devices only.
- ▶ The following acoustic connections / ear pieces were used:
 - Earhook
 - ThinTube 3.0
 - ThinTube 3.0 P


Special note for instruments with built-in lithium-ion rechargeable battery

- ▶ The runtime of all lithium-ion rechargeable batteries reduces over time. The estimates are based on fresh lithium-ion rechargeable battery capacity. Under normal operating conditions, the battery will retain up to 80 % of its initial capacity after 2 years of use. Please note that battery performance will vary depending on individual usage patterns and environmental conditions.



“Made for iPod”, “Made for iPhone”, and “Made for iPad” mean that an electronic accessory has been designed to connect specifically to iPod, iPhone, or iPad, respectively, and has been certified by the developer to meet Apple performance standards. Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards. Please note that the use of this accessory with iPod, iPhone, or iPad may affect wireless performance.

The information in this document contains general descriptions of the technical options available, which do not always have to be present in individual cases and are subject to change without prior notice. The required features should therefore be specified in each individual case at the time of conclusion of the respective contract.

 **Legal Manufacturer**
WSAUD A/S
Nymøllevej 6
3540 Lyngø
Denmark


0123

Order No. 04427-99T03-7600
© 03.2021, WSAUD A/S
All rights reserved

Subject to change
without prior notice

www.signia.net



WARNING

Choking hazard posed by small parts.

- ▶ This instrument is not intended for the fitting of infants, children under 3 years or persons of mental incapacity.



WARNING

Instrument has an output sound pressure level of 132 dB SPL or more. Risk of impairing the residual hearing of the user.

- ▶ Take special care when fitting this instrument.